

Outside Screw and Yoke Gate Valves

Outside screw and yoke gate valves are recommended for service indoors and in pits outdoors. They are not recommended for throttling service. The stem indicates at a glance whether or not the valve is open. Smaller sizes, 3/4 through 2 in. NPS inclusive, are of bronze. Large sizes, 2 1/2 through 14 in. NPS inclusive, are of iron, bronze mounted. One manufacturer makes valves of bronze up through the 3 in. size. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

Model XZ41X-PN16

Resilient Seated Gate Valves. 2 through 24 in. NPS. Valves have a rated working pressure of 232 psi (1600 kPa). Available with the following end connections.

Product Specification

| Model No | Valve Size | | End Connection |
|------------|------------------------------|---------------------------------------|---|
| | in | (mm) | |
| XZ41X-PN16 | 2, 2 1/2, 3, 4, 6, 8, 10, 12 | (50, 65, 80, 100, 150, 200, 250, 300) | Flange x Flange (ANSI, BS, EN, JIS) |
| XZ41X-PN16 | 14, 16, 18, 20, 24 | (350, 400, 450, 500, 600) | Flange x Flange (ANSI, BS, EN, JIS, DIN) |

| | |
|-------------------------------------|---|
| Company Name: | Jinan Meide Casting Co Ltd |
| Company Address: | Meide Science and Technology Park, Pingyin Industrial Park, Jinan, 250400 China |
| Company Website: | http://meide-casting.com |
| New/Updated Product Listing: | Yes |
| Listing Country: | China |
| Certification Type: | FM Approved |
| Class of Work: | 1120-OS&Y and NRS Gate Valves |